



NOTES:

Thread: 1/8" BSP

Connector: Deutsch DTM 2 Pin Connector

COMPATIBLE CONNECTORS:

H-MS-C - Motorsport Connector - F-Crimp

Unloaded Resistance Vs Temperature Data Table

Temp C	R Ohms	R +/- %	Ref Acc +/- C	Temp C	R Ohms	R +/- %	Ref Acc +/- C	Temp C	R Ohms	R +/- %	Ref Acc +/- C
-40	99,326	10.46	1.6	25	2,752	5.56	1.2	90	238.1	2.35	0.8
-35	71,332	10.00	1.5	30	2,205	5.28	1.2	95	203.9	2.13	0.7
-30	51,791	9.55	1.5	35	1,778	5.00	1.2	100	175.3	2.00	0.7
-25	37,994	9.11	1.5	40	1,443	4.72	1.1	105	151.3	2.24	0.8
-20	28,146	8.67	1.5	45	1,177	4.45	1.1	110	131.0	2.45	0.9
-15	21,044	8.25	1.4	50	965	4.18	1.1	115	113.9	2.63	1.0
-10	15,873	7.83	1.4	55	796	3.94	1.0	120	99.4	2.79	1.0
-5	12,073	7.42	1.4	60	660	3.71	1.0	125	87.0	2.92	1.1
0	9,256	7.02	1.3	65	551	3.47	1.0	130	76.4	3.03	1.2
5	7,153	6.72	1.3	70	462	3.24	0.9	135	67.3	3.11	1.2
10	5,572	6.43	1.3	75	389	3.01	0.9	140	59.4	3.18	1.3
15	4,373	6.14	1.3	80	329	2.79	0.8	145	52.6	3.22	1.3
20	3,457	5.85	1.3	85	279	2.57	0.8	150	46.7	3.24	1.4

EFI Hardware Mobile Apps



www.efihardware.com/apps.php