



NOTES:

Thread : 1/8 NPT
Temperature Range : -20 to 200 C
Housing Material : Stainless Steel
300mm Unterminated Flying Lead

Unloaded Resistance Vs Temperature Data Table

| Temp C | Ohms | V Volts | Temp C | R Ohms | V Volts |
|--------|--------|---------|--------|--------|---------|
| -20 | 72,300 | 4.932 | 90 | 1,239 | 2.767 |
| -10 | 44,360 | 4.890 | 100 | 954 | 2.441 |
| 0 | 28,050 | 4.828 | 110 | 743 | 2.131 |
| 10 | 18,220 | 4.740 | 120 | 586 | 1.847 |
| 20 | 12,140 | 4.619 | 130 | 467 | 1.592 |
| 30 | 8,281 | 4.461 | 140 | 377 | 1.369 |
| 40 | 5,769 | 4.261 | 150 | 150 | 1.174 |
| 50 | 4,099 | 4.019 | 160 | 252 | 1.006 |
| 60 | 2,967 | 3.740 | 180 | 175 | 0.745 |
| 70 | 2,184 | 3.430 | 200 | 125 | 0.556 |
| 80 | 1,633 | 3.101 | | | |

with 1k pull up resistor for MoTec M1 input

EFI Hardware Mobile Apps

